

## Accessories

### TS 35X7.5 2M/ST/ZN

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com



### Building installation wiring

For building installations, we offer a complete system that revolves around the 10×3 copper rail and comprises perfectly coordinated components: from installation terminal blocks, neutral conductor terminal blocks and distribution terminal blocks to comprehensive accessories such as busbars and busbar holders.

### General ordering data

Type	TS 35X7.5 2M/ST/ZN
Order No.	<a href="#">0383400000</a>
Version	Mounting rail, TS 35, TS 35 x 7.5, without slot, Steel, galvanized, chromium-plated
GTIN (EAN)	4008190088026
Qty.	2 m

## Data sheet

### Accessories TS 35X7.5 2M/ST/ZN

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technical data

### Dimensions and weights

Width	35 mm	Width (inches)	1.378 inch
Height	35 mm	Height (inches)	1.378 inch
Depth	7.5 mm	Depth (inches)	0.295 inch
Net weight	325 g		

### Material data

Material	Steel	Surface finish	galvanized, chromium-plated
Colour	Silver		

### System specifications

Version	without slot	Mounting rail	TS 35, TS 35 x 7.5
---------	--------------	---------------	--------------------

### Additional technical data

Installation advice	Direct mounting	Type of mounting	Screwed
---------------------	-----------------	------------------	---------

### Mounting rail

Short circuit strength corresponds to E-Cu wire	16 mm <sup>2</sup>	Thickness	1 mm
---	--------------------	-----------	------

### Rating data

Standards	DIN EN 60715
-----------	--------------

### Classifications

ETIM 3.0	EC001285	ETIM 4.0	EC001285
ETIM 5.0	EC001285	ETIM 6.0	EC001285
UNSPSC	30-21-18-01	eClass 5.1	27-14-06-04
eClass 6.2	27-14-11-43	eClass 7.1	27-14-11-43
eClass 8.1	27-14-11-43	eClass 9.0	27-14-11-43
eClass 9.1	27-40-06-02		

### Product information

Descriptive text ordering data	TS 35X7.5 2M/AL/BK: max. permitted rated current for PEN function = 125 A
--------------------------------	---

### Approvals

ROHS	Conform
------	---------

### Downloads

Brochure/Catalogue	<a href="#">CAT 1 TERM 16/17 EN</a>
Engineering Data	<a href="#">EPLAN, WSCAD, Zuken E3.S</a>