

## Connecting elements H10,0/22 EB

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com



- supplied loose in polybag
- Weidmüller colour code
- DIN colour code
- other colour code

### General ordering data

|            |  |
|------------|--|
| Type       | H10,0/22 EB                                      |
| Order No.  | <a href="#">0534200000</a>                       |
| Version    | Wire end ferrule, insulated, 15 mm, 12 mm, Ivory |
| GTIN (EAN) | 4008190033460                                    |
| Qty.       | 100 pc(s).                                       |
| Packaging  | loose  |

**Data sheet**

**Connecting elements  
H10,0/22 EB**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**

**Dimensions and weights**

|            |       |                |            |
|------------|-------|----------------|------------|
| Width      | 22 mm | Width (inches) | 0.866 inch |
| Net weight | 0.5 g |                |            |

**Technical data**

|         |           |
|---------|-----------|
| Version | insulated |
|---------|-----------|

**Wire-end ferrules**

|   |                    |                               |             |
|---|--------------------|-------------------------------|-------------|
| Collar diameter (D2)                    | 7.6 mm             | Colour code                   | Weidmüller  |
| Conductor cross-section                 | 10 mm <sup>2</sup> | Contact surface diameter (D1) | 4.5 mm      |
| Contact surface length (L2)             | 12 mm              | L1 in mm                      | 22 mm       |
| Metal sleeve thickness (S1)             | 0.2 mm             | Military designation          | T 20A 025 A |
| Plastic collar thickness (S2)           | 0.4 mm             | Stripping length              | 15 mm       |
| Wire connection cross section AWG, max. | AWG 7              |                               |             |

**Classifications**

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 3.0   | EC000005    | ETIM 4.0   | EC000005    |
| ETIM 5.0   | EC000005    | ETIM 6.0   | EC000005    |
| UNSPSC     | 31-16-31-02 | eClass 5.1 | 27-40-02-01 |
| eClass 6.2 | 27-40-02-01 | eClass 7.1 | 27-40-02-01 |
| eClass 8.1 | 27-40-02-01 | eClass 9.0 | 27-40-02-01 |
| eClass 9.1 | 27-40-02-01 |            |             |

**Approvals**

Approvals



ROHS Conform

**Downloads**

|                    |  |
|--------------------|--|
| Brochure/Catalogue | <a href="#">CAT 6 TOOLS 15/16 EN</a>     |
| Engineering Data   | <a href="#">EPLAN, WSCAD, Zuken E3.S</a> |